6000 liters tank in Stainless 304

265 000 SEK /st exkl moms

Additional information: Chemistry; 4 mild steel foot extensions; el. pneumatic outlet flap diameter 200 mm within a standard DN 300 socket; inspection door without dead space in the cylinder
Volumetric volume (L): 6.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Number of revolutions: 8,40

Power: 37
Internal diameter tank: 2.150 mm
Cylinder height: 2.150 mm
Total height of tank: 5.000 mm

SKU: 411983

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Product Description

Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: ATM – atmospheric
Configuration: single-skin
Mobile Tank: No, it is not.
Övrig information: Chemistry; 4 mild steel foot extensions; el. pneumatic outlet flap diameter 200 mm within a standard DN 300 socket; inspection door without dead space in the cylinder
Agitator: No
Complete Drainage: Yes
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 6000

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 2,150 mm
Internal diameter: 2,150 mm
Total Height: 5,000 mm

Stirrer

Power (kW): 37
Speed (RPM): 8,40

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer
Isolated: No

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor