

6000 liters tank in Stainless 304



215 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 6.000 L

Pressure in tank: ATM - atmospheric

Max. temperature (°C): 20 °C

Min. temperature (°C): 5 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger



Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 4 adjustable feet

Heat exchanger: RVS 304

Insulation material: Rockwool

Outer jacket (ornamental wall): RVS 304

Spray ball: RVS 304

Manway(s): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Top: 2,50 mm

Cylinder: 3 mm

Bottom: 3 mm

Cylinder: 2

Insulation body: yes

Bottom: 2

Insulation bottom/sides: yes

Insulation thickness: 80



Internal diameter tank: 1.750 mm

Distance from outlet to ground: 1.765 mm

Outer diameter tank: 1.905 mm

Cylinder height: 2.500 mm

Feet height: 1.765 mm

Empty weight tank: 1.200

SKU: 451949-1

Mer information



Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated with heat-exchanger

Max. Service Temperature: 20 °C

Min. Operating Temperature: 5 °C

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 6000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Food-grade: Yes

Tank Outlet: inside Ø 50 mm

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Exterior cladding: RVS 304



Tank Dimensions

Cylinder Height: 2.500 mm
Height on legs: 1.765 mm
Internal diameter: 1.750 mm
Outlet Height to Ground: 1.765 mm
Outer diameter: 1.905 mm

Stirrer

Motor Position: at the top
Agitator Type: propeller agitator

Tjocklek på tank

Bottom: 3 mm
Cylinder: 3 mm
Top: 2,50 mm

Outer Cladding and Insulation Thickness

Insulation bottom/end caps: Yes
Jacket insulation: Yes
Insulation material: Rockwool

Mer

Heat Exchanger: RVS 304
Cylinder OW: 2
Bottom OW: 2
Insulation Thickness OW: 80
Isolated: Yes
Weight: 1.200