

60000 liters tank in Stainless 304



283 000 SEK /st exkl moms

Article type: second-hand storage tank

Additional information: The previous product was softened water; traces of product present in the tank. The tank is in very good condition and was built by La Garrec.

Volumetric volume (L): 60.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 120 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: insulated



Heat exchanger: no

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: flat sloping 1,71 °

Total discharge: yes

Insulation material: Rockwool

Outer jacket (ornamental wall): steel-epoxy

Manway(s): RVS 304L

Gasket manway(s): unknown

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 2

Position of manway: cylinder

Height manhole 1 (mm): 500 mm

Position 2nd manway: at the top

Height manhole 2 (mm): 500

Tank outlet: inside Ø 65 mm

Tank location: outside

Agitator: no, optional

Insulation top: yes

Insulation body: yes

finish of the outer jacket: riveted

Insulation thickness: 100

Internal diameter tank: 2.870 mm

Outer diameter tank: 3.090 mm

Cylinder height: 9.750 mm

Total height of tank: 10.500 mm



Empty weight tank: 3.800

SKU: 565943

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated

Max. Service Temperature: 120 °C

Min. Operating Temperature: -10 °C

Mobile Tank: No, it is not.

Övrig information: The previous product was softened water; traces of product present in the tank. The tank is in very good condition and was built by La Garrec.

Agitator: No

Tank Shape: cylindrical

Complete Drainage: Yes

Bottom Type: flat sloping 1,71 °

Heating / Cooling: No

Contact Surface: SS AISI 304L (V2A)

Volume in liters: 60000



Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Food-grade: Yes

Tank Outlet: inside Ø 65 mm

Technical Drawing Available: Yes

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304L

Insulation material: Rockwool

Exterior cladding: steel-epoxy

Tank Dimensions

Cylinder Height: 9.750 mm

Internal diameter: 2,870 mm

Total Height: 10.500 mm

Outer diameter: 3.090 mm

Outer Cladding and Insulation Thickness

External jacket finish: riveted

Jacket insulation: Yes

Insulation material: Rockwool

Mer

Insulation material: Yes

Insulation Thickness OW: 100

Isolated: Yes

Weight: 3.800