

605 liter tank in Stainless 304



106 000 SEK /st exkl moms

Additional information: Stainless steel 304 frame; manhole diameter approx. 395 mm; some residues of previous content

Volumetric volume (L): 605 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 133 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 45 L

Max Overpressure: 6 Bar

Max. working temperature: 65 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: DN40 DIN 11851

Agitator: yes

Number of revolutions: 710

Power: 3

Internal diameter tank: 880 mm

Total height of tank: 2.780 mm

Total outer width: 1.320 mm

Total outer length: 1.200 mm

SKU: 576233



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 133 °C

Mobile Tank: No, it is not.

Övrig information: Stainless steel 304 frame; manhole diameter approx. 395 mm; some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Additional Information2: agitator

Agitator: Yes

Overpressure: 3 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 605

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Internal diameter: 880 mm

Total Height: 2,780 mm

Stirrer

Power (kW): 3

Speed (RPM): 710

Mer

Isolated: Yes