

6100 liter tank in Acid-proof 316



126 000 SEK /st exkl moms

Additional information: Chemistry; Insulation only around the cylindrical part of the tank; flanged to the outlet is a reducing fitting (reduced to an inside pipe diameter of 50 mm; fitting components made of plastic); 1 pump is included (see photos)

Volumetric volume (L): 6.100 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 80 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 330 L

Max. working temperature: 80 °C

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: flange DN80

Agitator: yes

Number of revolutions: 725 / 1450

Power: 3.6 / 5.3

Cylinder: 6,20 mm

Bottom: 4 mm

Internal diameter tank: 1.990 mm

Outer diameter tank: 2.170 mm

Cylinder height: 1.800 mm

Total height of tank: 3.650 mm

SKU: 420692



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: ATM – atmospheric

Configuration: insulated with heat-exchanger

Max. Service Temperature: 80 °C

Mobile Tank: No, it is not.

Övrig information: Chemistry; Insulation only around the cylindrical part of the tank; flanged to the outlet is a reducing fitting (reduced to an inside pipe diameter of 50 mm; fitting components made of plastic); 1

Additional Information2: pump is included (see photos); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Complete Drainage: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 6100

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.800 mm
Internal diameter: 1,990 mm
Total Height: 3.650 mm
Outer diameter: 2.170 mm

Stirrer

Power (kW): 3.6 / 5.3
Speed (RPM): 725 / 1450

Tjocklek på tank

Bottom: 4 mm
Cylinder: 6,20 mm

Mer

Isolated: Yes