634 liter tank in Syrafast 316

164 000 SEK /st exkl moms

Additional information: Diameter of hand hole approx. 140 mm; temperature control unit is a Regloplas 90 XL (water as heat transfer medium)
Volumetric volume (L): 634 L
Pressure in tank: pressure
Max. pressure (Bar): 2,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 2,50 Bar

Max. temperature (°C): 138 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 66 L
Max Overpressure: 2,50 Bar

Max. working temperature: 138 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: DN32 DIN 11851
Agitator: yes
Number of revolutions: 695

Power: 0,90
Internal diameter tank: 890 mm
Outer diameter tank: 1.040 mm
Total height of tank: 2.150 mm

SKU: 567062

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure
Configuration: insulated with heat-exchanger
Max. Service Temperature: 138 °C
Mobile Tank: No, it is not.
Övrig information: Pharmacy; Handhole diameter approx. 140 mm; we cannot provide any guarantees regarding the heating/cooling jacket; we cannot provide any guarantees regarding the agitator
Additional Information2: give any guarantees about the agitator
Agitator: Yes
Overpressure: 2,50 bar
Complete Drainage: Yes
Vacuum Pressure: 2,50 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 634

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Internal diameter: 890 mm
Total Height: 2,150 mm
Outer diameter: 1,040 mm

Stirrer
Power (kW): 0,90
Speed (RPM): 695

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor