

650 liter tank in 304 stainless steel



90 000 SEK /st exkl moms

Additional information: pharmacy; Metallic discoloration inside

Volumetric volume (L): 650 L

Pressure in tank: pressure

Max. pressure (Bar): 1,50 Bar



Min. pressure (Bar): 1,50 Bar

Max. temperature (°C): 170 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 8 Bar

Max. working temperature: 170 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 25

Agitator: yes

Number of revolutions: 1.415

Power: 1

Cylinder: 6 mm

Bottom: 5 mm

Internal diameter tank: 900 mm

Outer diameter tank: 1.040 mm

Cylinder height: 900 mm

Total height of tank: 2.380 mm

SKU: 395204



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure

Configuration: isolert med varmeveksler

Max. Service Temperature: 170 °C

Mobile Tank: No, it is not.

Övrig information: pharmacy; metallic discolourations inside; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 1,50 bar

Complete Drainage: Yes

Vacuum Pressure:

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 650

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 900 mm
Internal diameter: 900 mm
Total Height: 2,380 mm
Outer diameter: 1,040 mm

Stirrer

Power (kW): 1
Speed (RPM): 1.415

Tjocklek på tank

Bottom: 5 mm
Cylinder: 6 mm

Mer

Heat Exchanger: RVS 304
Isolated: Yes