6500 liter tank in Acid-proof 316

212 000 SEK /st exkl moms

Additional information: Chemistry; bump at the insulation jacket; manhole cover plated
Volumetric volume (L): 6.500 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2,60 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 180 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 200 °C
Type HE on the bottom: half pipe welded onto the outside of the innertank
Type HE on the cylinder: half pipe welded onto the outside of the innertank
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom
Outlet of tank: DN50 DIN 11851

Agitator: yes
Number of revolutions: 15 - 61
Power: 9,20
Internal diameter tank: 2.000 mm
Outer diameter tank: 2.180 mm

Cylinder height: 1.500 mm
Total height of tank: 5.400 mm

SKU: 423947

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 200 °C
Mobile Tank: No, it is not.
Övrig information: Chemistry; bump at the insulation jacket;manhole cover plated; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 2,60 bar
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 6500

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions

Cylinder Height: 1.500 mm
Internal diameter: 2,000 mm
Total Height: 5,400 mm
Outer diameter: 2,180 mm

Stirrer

Power (kW): 9,20
Speed (RPM): 15 – 61

Mer

Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor