

6510 liters tank in Stainless 304



186 000 SEK /st exkl moms

Additional information: ethanol; a number of connections were changed by the former operator (not mentioned in the TÜV-certificates); tank on 3 support brackets made of aus Fe (not on 4 support brackets as discribed in the drawing); heating coil cylinder only in the lower cylindrical part; insulation jacket with cut-outs and dents; some residues of previous content

Volumetric volume (L): 6.510 L



Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 165 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 34 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 165 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: flange DN65

Agitator: yes

Number of revolutions: 73

Power: 5,50

Top: 8 mm

Cylinder: 7 mm

Bottom: 7 mm

Internal diameter tank: 1.900 mm

Cylinder height: 1.800 mm

Total height of tank: 4.450 mm



SKU: 391067

Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 165 °C

Mobile Tank: No, it is not.

Övrig information: ethanol; a number of connections were changed by the former operator (not mentioned in the TÜV-certificates); tank on 3 support brackets made of aus Fe (not on 4 support brackets as discribed in the

Additional Information2:

Agitator: Yes

Overpressure: 2 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 6510

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.



Material Overview

Material: Stainless steel 304

Tank Dimensions

Cylinder Height: 1.800 mm

Internal diameter: 1.900 mm

Total Height: 4,450 mm

Stirrer

Power (kW): 5,50

Speed (RPM): 73

Tjocklek på tank

Bottom: 7 mm

Cylinder: 7 mm

Top: 8 mm

Mer

Heat Exchanger: RVS 304

Isolated: Yes