680 liter tank in 304 stainless steel

208 000 SEK /st exkl moms

Additional information: Pharmacy; The total height includes the 4 loose foot extensions (length approx. 900 mm each); some residues of previous content
Volumetric volume (L): 680 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 120 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 28 L
Max Overpressure: 3 Bar

Max onderdruk: 1 Bar
Max. working temperature: 120 °C
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Outlet of tank: 50
Agitator: yes
Power: 3
Top: 3,20 mm

Cylinder: 4 mm
Bottom: 2,80 mm
Internal diameter tank: 820 mm
Outer diameter tank: 955 mm
Cylinder height: 1.000 mm

Total height of tank: 3.250 mm

SKU: 426008

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Stainless steel 304
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 120 °C
Mobile Tank: No, it is not.
Övrig information: Pharmacy; The total height includes the 4 loose foot extensions (length approx. 900 mm each); some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we
Additional Information2: can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 680

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Cylinder Height: 1.000 mm
Internal diameter: 820 mm
Total Height: 3.250 mm
Outer diameter: 955 mm

Stirrer
Power (kW): 3

Tjocklek på tank
Bottom: 2,80 mm
Cylinder: 4 mm
Top: 3,20 mm

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor