

680 liter tank in 304 stainless steel



208 000 SEK /st exkl moms

Additional information: Pharmacy; The total height includes the 4 loose foot extensions (length approx. 900 mm each); some residues of previous content

Volumetric volume (L): 680 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 120 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 15 L

Max Overpressure: 3 Bar

Max onderdruk: 1 Bar

Max. working temperature: 120 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 50

Agitator: yes

Number of revolutions: 255 / 510

Power: 1.1 / 1.4

Top: 3,20 mm

Cylinder: 4 mm

Bottom: 2,80 mm

Internal diameter tank: 820 mm

Outer diameter tank: 955 mm

Cylinder height: 1.000 mm

Total height of tank: 3.250 mm

SKU: 425945



Mer information

Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 120 °C

Mobile Tank: No, it is not.

Övrig information: Pharmacy; The total height includes the 4 loose foot extensions (length approx. 900 mm each); some residues of previous content; we can't give any guarantees about the heating/cooling jacket; we

Additional Information2: can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 3 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 680

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304



Tank Dimensions

Cylinder Height: 1.000 mm
Internal diameter: 820 mm
Total Height: 3.250 mm
Outer diameter: 955 mm

Stirrer

Power (kW): 1.1 / 1.4
Speed (RPM): 255 / 510

Tjocklek på tank

Bottom: 2,80 mm
Cylinder: 4 mm
Top: 3,20 mm

Mer

Isolated: Yes