

689 liter tank in Syrafast 316



199 000 SEK /st exkl moms

Additional information: Pharmacy; Slight metallic discoloration inside the tank; Outlet fitting incomplete

Volumetric volume (L): 689 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 63 L

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Max. working temperature: 150 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 38

Agitator: yes

Number of revolutions: 343

Power: 0,55

Top: 4,80 mm

Cylinder: 7 mm

Bottom: 5,20 mm

Internal diameter tank: 800 mm

Outer diameter tank: 950 mm

Cylinder height: 1.180 mm

Total height of tank: 2.400 mm

SKU: 412139



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature:

Mobile Tank: No, it is not.

Övrig information: Pharmacy; Slight metallic discoloration inside the tank; Outlet fitting incomplete; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 6 bars

Complete Drainage:

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 689

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.180 mm
Internal diameter: 800 mm
Total Height: 2,400 mm
Outer diameter: 950 mm

Stirrer

Power (kW): 0,55
Speed (RPM): 343

Tjocklek på tank

Bottom: 5,20 mm
Cylinder: 7 mm
Top: 4,80 mm

Mer

Isolated: Yes