

7000 liter tank in Stainless 304



120 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 7.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 3 non adjustable feet

Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 410 mm
Tank outlet: inside Ø 50 mm

Outlet type: DIN11851
Outlet of tank: DN50
Total outlet valve: yes
Agitator: yes
Agitator type: propeller agitator

Position engine: at the top
Number of revolutions: 450
Power: 1,50
Voltage: 400 V - three-phase
Current: 5,50

Top: 4 mm
Insulation body: yes
Insulation bottom/sides: yes
finish of the outer jacket: welded



Insulation thickness: 50

Internal diameter tank: 1.742 mm

Distance from outlet to ground: 400 mm

Outer diameter tank: 1.800 mm

Cylinder height: 3.500 mm

Feet height: 980 mm

Total height of tank: 5.740 mm

Empty weight tank: 850

SKU: 489429

Mer information

Product Description

Food-grade: Yes

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated

Mobile Tank: No, it is not.

Övrig information: we can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: conical

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 7000



Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: No, it is not.
Food-grade: Yes
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: No, it is not.
Outlet Type: DIN11851
Outlet Valve: Yes

Material Overview

Material: Stainless steel 304
Fixing point(s): RVS 304
Insulation material: Rockwool
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Exterior cladding: RVS 304

Tank Dimensions

Cylinder Height: 3.500 mm
Height on legs:
Internal diameter:
Outlet Height to Ground: 400 mm
Total Height: 5.700 mm
Outer diameter: 1.800 mm

Stirrer

Power (kW): 1,50
Motor Position: at the top
Agitator Type: propeller agitator
Speed (RPM): 450
Voltage: three-phase

Tjocklek på tank

Top: 4 mm

Outer Cladding and Insulation Thickness

External jacket finish: welded

Insulation bottom/end caps: Yes

Jacket insulation: Yes

Insulation material: Rockwool

Mer

Insulation Thickness OW: 50

Isolated: Yes

Weight: 800