721 liter tank in Syrafast 316

114 000 SEK /st exkl moms

Additional information: pharmacy
Volumetric volume (L): 721 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 133 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 56 L
Max Overpressure: 1 Bar

Max onderdruk: 1 Bar
Max. working temperature: 133 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: in the bottom

Outlet of tank: available
Agitator: yes
Number of revolutions: 100 - 500
Power: 1,10
Internal diameter tank: 950 mm

Outer diameter tank: 1.100 mm
Cylinder height: 750 mm
Total height of tank: 2.520 mm

SKU: 409679

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: isolert med varmeveksler
Max. Service Temperature: 133 °C
Mobile Tank: No, it is not.
Övrig information: pharmacy; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 721

Equipment

Product Dokument finns: No
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Tank Dimensions

Cylinder Height: 750 mm
Internal diameter: 950 mm
Total Height: 2,520 mm
Outer diameter: 1.100 mm

Stirrer

Power (kW): 1,10
Speed (RPM): 100 – 500

Mer

Heat Exchanger: RVS 304
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se