

730 liter tank in Acid-proof 316



173 000 SEK /st exkl moms

Additional information: Pharmaceutical chemistry; Half-coil for heating/cooling around the lower cylindrical area and the lower bottom; hand hole diameter 150 mm; outlet fitting incomplete; Device for load cells under the feet (probably 3 load cells available; loose load cells were not taken into account when specifying the total height), insulation jacket partially cut open in the area of the lower bottom; Technical documents are available from the manufacturer and could be purchased directly from the manufacturer if



required; bump at the insulation jacket; handhole cover is missing

Volumetric volume (L): 730 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 4 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 12 L

Max Overpressure: 16 Bar

Max onderdruk: 1 Bar

Max. working temperature: 200 °C

Type HE on the bottom: half pipe welded onto the outside of the innertank

Type HE on the cylinder: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 53

Agitator: yes

Number of revolutions: 270

Power: 1,50

Internal diameter tank: 790 mm

Outer diameter tank: 1.080 mm

Cylinder height: 1.200 mm

Total height of tank: 2.950 mm

Empty weight tank: 700

SKU: 405236

Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: insulated with heat-exchanger

Max. Service Temperature: 200 °C

Mobile Tank: No, it is not.

Övrig information: Pharmaceutical chemistry; Half-coil for heating/cooling around the lower cylindrical area and the lower bottom; hand hole diameter 150 mm; outlet fitting incomplete;

Device for load cells under the

Additional Information2:

Agitator: Yes

Overpressure: 4 bars

Complete Drainage:

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 730

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: Yes

Technical Drawing Available: No, it is not.



Material Overview

Material: Acid-resistant 316

Tank Dimensions

Cylinder Height: 1.200 mm

Internal diameter: 790 mm

Total Height: 2,950 mm

Outer diameter: 1,080 mm

Stirrer

Power (kW): 1,50

Speed (RPM): 270

Mer

Isolated: Yes

Weight: 700