733 liter tank in Syrafast 316

186 000 SEK /st exkl moms

Additional information: Device for holding load cells under the feet (the load cells themselves are no longer present)
Volumetric volume (L): 733 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 6 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 55 L
Max Overpressure: 6 Bar

Max onderdruk: 1 Bar
Max. working temperature: 150 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: 25
Agitator: yes

Number of revolutions: 910
Power: 1,50
Internal diameter tank: 880 mm
Outer diameter tank: 1.030 mm
Total height of tank: 2.250 mm

SKU: 489982

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature:
Mobile Tank: No, it is not.
Övrig information: Pharmacy; Device for holding load cells under the feet (the load cells themselves are no longer present); we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees
Additional Information2: about the agitator
Agitator: Yes
Overpressure: 6 bars
Complete Drainage:
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 733

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions
Internal diameter: 880 mm
Total Height: 2.250 mm
Outer diameter: 1,030 mm

Stirrer
Power (kW): 1,50
Speed (RPM): 910

Mer
Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor