

780 liter tank in Acid-proof 316





73 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type K2-SL

Volumetric volume (L): 780 L

Max. density P (kg/m³): 1.200

Ra inner weld: 0,80

Finish stainless steel: 2b

Pressure in tank: ATM - atmosferic

Design pressure (Bar): 0,05 Bar

Max. temperature (°C): 100 °C

Min. temperature (°C): -10 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes



Inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 400 mm

CIP spray ball: no, optional

Max. CIP temp. (°C): 30 °C

Tank outlet: inside Ø 50 mm

Outlet type: DIN11851 male

Total outlet valve: no, optional

Agitator: no, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 2 mm

Distance from outlet to ground: 342 mm

Outer diameter tank: 950 mm

Cylinder height: 1.000 mm

Feet height: 516 mm

Total height of tank: 1.782 mm

Empty weight tank: 97

SKU: 378866

Mer information



Product Description

Food-grade: Yes
Material: Acid-resistant 316
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank:
Tank design pressure: 0,05 bar
Stainless steel finish: 2b
Configuration: single-skin
Max. Service Temperature: 100 °C
Maximum Product Density: 1200
Min. Operating Temperature: -10 °C
Mobile Tank: No, it is not.
Agitator: No
Ra Internal Weld: 0,80
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical 15 °
Heating / Cooling: No
Contact Surface: SS AISI 316L (V4A)
Volume in liters: 780

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Inspected by: TUV
Tank Outlet: inside Ø 50 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851 male

Material Overview

Material: Acid-resistant 316
Fixing point(s): RVS 304L



Tank Dimensions

Cylinder Height: 1.000 mm

Height on legs: 516 mm

Outlet Height to Ground: 342 mm

Total Height: 1.782 mm

Outer diameter: 950 mm

Tjocklek på tank

Bottom: 2 mm

Cylinder: 2 mm

Top: 2 mm

Mer

Isolated: No

Weight: 97