

8000 liter tank in Acid-proof 316



219 000 SEK /st exkl moms

Additional information: Chemistry; 4 support brackets, Fe; double jacket blasted and primed; Type plate probably not available

Volumetric volume (L): 8.000 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 135 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 600 L

Max. working temperature: 135 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: flange DN100

Agitator: yes

Number of revolutions: 140

Power: 30

Cylinder: 13 mm

Bottom: 10 mm

Internal diameter tank: 2.200 mm

Outer diameter tank: 2.300 mm

Cylinder height: 1.830 mm

Total height of tank: 5.100 mm

SKU: 423623



Mer information

Product Description

Material: Acid-resistant 316

Model: Vertical

New / Used: Used

Operating Pressure in Tank: pressure and vacuum

Configuration: single jacketed with heat-exchanger

Max. Service Temperature: 135 °C

Mobile Tank: No, it is not.

Övrig information: Chemistry; 4 support brackets, Fe; double jacket blasted and primed; Type plate probably not available; we can't give any guarantees about the agitator

Agitator: Yes

Overpressure: 2 bars

Complete Drainage: Yes

Vacuum Pressure: 1 bar

Pressure Vessel: Yes

Heating / Cooling: Yes

Contact Surface: SS AISI 316 (V4A)

Volume in liters: 8000

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316



Tank Dimensions

Cylinder Height: 1.830 mm
Internal diameter: 2,200 mm
Total Height: 5.100 mm
Outer diameter: 2,300 mm

Stirrer

Power (kW): 30
Speed (RPM): 140

Tjocklek på tank

Bottom: 10 mm
Cylinder: 13 mm

Mer

Isolated: No