

8100 liter tank in Stainless 304



109 000 SEK /st exkl moms

Article type: brand new storage tank - type K-SL

Volumetric volume (L): 8.100 L

Max. density P (kg/m³): 1.200

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no



Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 15 °

Total discharge: yes

Fixation points: 4 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Manway(s): RVS 304

Gasket manway(s): EPDM

Valve: RVS 316L

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 500 mm

CIP spray ball: no

Tank outlet: inside Ø 65 mm

Outlet type: DIN11851

Total outlet valve: no, optional

Adjustable legs: yes

Agitator: no, optional

Top: 1,50 mm

Cylinder: 1,50 mm

Bottom: 2 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 1.874 mm

Cylinder height: 2.750 mm

Feet height: 630 mm

Total height of tank: 3.870 mm

Empty weight tank: 800



SKU: 460920

Mer information

Product Description

Food-grade: Yes
Material: Stainless steel 304
Model: Vertical
New / Used: Newly manufactured
Operating Pressure in Tank:
Configuration: single-skin
Maximum Product Density: 1200
Mobile Tank: No, it is not.
Agitator: No
Tank Shape: cylindrical
Complete Drainage:
Bottom Type: conical 15 °
Heating / Cooling: No
Contact Surface: SS AISI 304 (V2A)
Volume in liters: 8100

Equipment

Agitator flange: No
Nameplate: Yes
Food-grade: Yes
Tank Outlet: inside Ø 65 mm
Technical Drawing Available: Yes
Outlet Type: DIN11851



Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Tank Dimensions

Cylinder Height: 2,750 mm

Height on legs: 630 mm

Outlet Height to Ground: 250 mm

Total Height: 3,870 mm

Outer diameter: 1,874 mm

Tjocklek på tank

Bottom: 2 mm

Cylinder: 1,50 mm

Top: 1,50 mm

Mer

Isolated: No

Weight: 800