

90 liter tank in stainless steel 304



42 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: closed tank on 4 stainless wheels; propellor agitator in SS stainless-steel AISI 304 (V2A); 0,37 kW - 1.500 rpm; lantern ring in stainless-steel; discharge valve DIN11851; CIP sprayball 1/2; we can't give any guarantees about the agitator

Volumetric volume (L): 90 L

Max. density P (kg/m³): 1.000

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Top type: half hinging lid

Shape of tank: cylindrical

Bottom type: flat

Total discharge: yes

Fixation points: 4 casters

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Tank outlet: inside Ø 32 mm



Outlet type: DIN11851

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Number of revolutions: 1.320

Power: 0,37

Voltage: 220 V - mono

Top: 2,50 mm

Cylinder: 1,50 mm

Bottom: 1,50 mm

Internal diameter tank: 475 mm

Distance from outlet to ground: 375 mm

Outer diameter tank: 520 mm

Cylinder height: 550 mm

Total height of tank: 1.350 mm

Empty weight tank: 40

SKU: 375473

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Configuration: single-skin

Maximum Product Density: 1000

Mobile Tank: No, it is not.

Övrig information: closed tank on 4 stainless wheels; propeller agitator in SS stainless-steel AISI 304 (V2A); 0,37 kW – 1.500 rpm; lantern ring in stainless-steel; discharge valve DIN11851; CIP sprayball 1/2; we

Additional Information2: can't give any guarantees about the agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: flat

Heating / Cooling: No

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 90

Equipment

Product Dokument finns: No

Agitator flange: No

Nameplate: No, it is not.

Tank Outlet: inside Ø 32 mm

Technical Drawing Available: No, it is not.

Outlet Type: DIN11851

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)



Tank Dimensions

Cylinder Height: 550 mm

Internal diameter: 475 mm

Outlet Height to Ground: 375 mm

Total Height: 1.350 mm

Outer diameter: 520 mm

Stirrer

Power (kW): 0,37

Motor Position: at the top

Agitator Type: propeller agitator

Speed (RPM): 1.320

Voltage: 220 V – mono

Tjocklek på tank

Bottom: 1,50 mm

Cylinder: 1,50 mm

Top: 2,50 mm

Mer

Isolated: No

Weight: 40