

9000 liters tank in stainless steel 304



192 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: half coil for heating on the cylinder and on the bottom and a tube heat exchanger in the tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 13.500 L

Pressure in tank: ATM - atmospheric

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes



Insulation: yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Bottom outlet: yes

Total discharge: yes

Fixation points: 4 loadcells

Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Position HE: the complet cilinder

Type HE: spiral pipes inside the tank

Type of HE on the bottom: half pipe welded onto the outside of the innertank

Heat exchanger bottom connected with cylinder: yes

Connection of the bottom to the cylinder: binnen isolatie

Heat exchanger: RVS 304

Insulation material: rockwool

Outer jacket (ornamental wall): RVS 304L

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)

Suitable for food industry: no

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: headside

Hinged lid: yes

Tank outlet: inside Ø 60 mm

Agitator: yes

Agitator type: 4 blade impeller

Position engine: at the top



Number of revolutions: 25

Power: 4

Voltage: 380 V - three-phase

Internal diameter tank: 2.200 mm

Distance from outlet to ground: 220 mm

Outer diameter tank: 2.300 mm

Cylinder height: 2.500 mm

Total height of tank: 3.900 mm

Empty weight tank: 1.200

SKU: 485897

Mer information



Product Description

Material: Stainless steel 304

Model: Vertical

New / Used: Used

Operating Pressure in Tank:

Configuration: insulated with heat-exchanger

Mobile Tank: No, it is not.

Övrig information: half coil for heating on the cylinder and on the bottom and a tube heat exchanger in the tank; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the

Additional Information2: agitator

Agitator: Yes

Tank Shape: cylindrical

Complete Drainage:

Bottom Type: dish

Heating / Cooling: Yes

Contact Surface: SS AISI 304 (V2A)

Volume in liters: 13500

Equipment

Product Dokument finns: No, it is not.

Agitator flange: No

Nameplate: No, it is not.

Tank Outlet: inside Ø 60 mm

Technical Drawing Available: No, it is not.

Material Overview

Material: Stainless steel 304

Fixing point(s): RVS 304

Insulation material: Rockwool

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Exterior cladding: RVS 304L



Tank Dimensions

Cylinder Height: 2,500 mm

Internal diameter: 2,200 mm

Outlet Height to Ground: 220 mm

Total Height: 3,900 mm

Outer diameter: 2,300 mm

Heat exchangers

Position värmeväxlare: the complete cylinder

Type of Heat Exchanger on Cylinder: half pipe welded onto the outside of the innertank

Bottom Heat Exchanger Type: half pipe welded onto the outside of the innertank

Stirrer

Power (kW): 4

Motor Position: at the top

Agitator Type: 4 blade impeller

Speed (RPM): 25

Voltage: 380 V – three-phase

Outer Cladding and Insulation Thickness

Insulation material: Rockwool

Mer

Heat Exchanger: RVS 304

Isolated: Yes

Weight: 1.200