920 liter tank in Acid-proof 316

173 000 SEK /st exkl moms

Volumetric volume (L): 920 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor

Max. temperature (°C): 130 °C

Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes

Mobile tank: no
Total discharge: yes
Volume: 70 L
Max Overpressure: 6 Bar
Max onderdruk: 1 Bar

Max. working temperature: 140 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 55
Agitator: yes

Number of revolutions: 412
Power: 0,75
Top: 4,50 mm
Cylinder: 5,70 mm
Bottom: 6,50 mm

Internal diameter tank: 988 mm
Outer diameter tank: 1.270 mm
Cylinder height: 906 mm
Total height of tank: 2.100 mm

SKU: 443348

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Mer information

Product Description

Material: Acid-resistant 316
Model: Vertical
New / Used: Used
Operating Pressure in Tank: pressure and vacuum
Configuration: insulated with heat-exchanger
Max. Service Temperature: 130 °C
Mobile Tank: No, it is not.
Övrig information: pharmacy; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator
Agitator: Yes
Overpressure: 3 bars
Complete Drainage: Yes
Vacuum Pressure: 1 bar
Pressure Vessel: Yes
Heating / Cooling: Yes
Contact Surface: SS AISI 316 (V4A)
Volume in liters: 920

Equipment

Product Dokument finns: No, it is not.
Agitator flange: No
Nameplate: Yes
Technical Drawing Available: No, it is not.

Material Overview

Material: Acid-resistant 316

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Tank Dimensions

Cylinder Height: 906 mm
Internal diameter: 988 mm
Total Height: 2.100 mm
Outer diameter: 1.270 mm

Stirrer

Power (kW): 0,75
Speed (RPM): 412

Tjocklek på tank

Bottom: 6,50 mm
Cylinder: 5,70 mm
Top: 4,50 mm

Mer

Isolated: Yes

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Läs våra köpvillkor